



Concrete Checklist

Christopher G. Hill
The Law Office of Christopher G. Hill, PC
804.205.5155
chrisghill@constructionlawva.com

General Rules

- Wear Protective Clothing
 - eye protection
 - snug-fitting clothing
- Guard all protruding reinforcing steel

Equipment and Tools

- Powered, rotating-type concrete trowels that are manually guided have a control switch that automatically shuts it off if operators hands removed from handles
- Sandblasting Operations: provide respirators for employees
- Steel-toe boots when handling concrete block
- When using gasoline powered concrete cutters, buggies, and trowels, ensure that enclosed spaces are adequately ventilated
- Employees cannot ride concrete buckets

Cast-in Place Concrete

- Inspect erected shoring equipment immediately prior to, during and immediately after concrete placement.
- Leave forms and shores in place until employer determines that the concrete can support its weight and superimposed loads.

Precast Concrete

- Support precast concrete wall units, structural framing, and tilt-up wall panels
- Lifting hardware capable of supporting at least 5 times maximum intended load

Lift-Slab Construction Operations

- Jacking equipment has safety factor of 2.5
- Maximum number of manually controlled jacks on one slab = 14
- Synchronize jacking operations

During jacking, only those employees required for jacking and to secure slabs permitted under slab

Masonry Construction

- Establish limited access zone on side without scaffoldings
 - Equal to height of wall to be constructed plus 4 feet
 - Equal to entire length of the wall
- If masonry wall over 8 feet tall, brace or support it

Please check out my [Construction Law Musings Blog](#) for more on Virginia construction law and other topics.